

Fiberglass Shingle Roof

Each shingle attached with six fasteners, backed by 20year limited warranty.

2 Asphalt Laminated Reinforced Shingle Underlayment

In addition to a layer of 15-lb roofing felt.

3 Oriented Strand Board Roof Sheathing

Engineered to resist racking and shape distortion under high wind.

Truss Roof Rafter System

With double rafters within 3' of front & rear. (Approved for hurricane zones I, II & III) Solid one-piece structural center beams.

5 Blown Cellulose Ceiling Insulation

Fire retardant and formaldehyde-free.

Insulated Flex-Duct System

Fiber reinforced mastic sealed airtight insulated flexduct system with sealed interior risers insulated with fiberglass.

7 Ventilated Roof Cavity

In addition to a whole house ventilation system.

Vinyl Lap Siding

50-year limited warranty: won't dent, rot, chip or corrode.

9 3/8" Structural Sheathing Under Lap Siding
Adds strength and extra insulation to walls.

Fiberglass Exterior Wall Insulation

For maximum energy efficiency.

2" x 6" Exterior Walls

With 26-gauge uplift straps attached to the floor and rafters.

2" x 4" Interior Walls

Gypsum board covered with decorative wall vinyls

13 Double Marriage Walls

Walls from each side of the home join together at the center line forming an double wall to provide superior structural stability.

Painted Gypsum Interior Walls

Or optional painted tape and textured walls.

Oriented Strand Board Floor Decking

Langboard OSB comes with a 10-year limited warranty against delamination.

Fiberglass Blanket Floor Insulation

A one-piece blanket of insulation covers each section to provide the highest amount of energy efficiency.

17 Transverse Floor Construction

Tongue-and-groove floor decking.

Reinforced Polyvinyl Bottom Board

Helps eliminate moisture infiltration and air seepage.

10 Solid Steel I-Beam

With a steel front header frame member.

Tie-Down Connectors

Vertical, horizontal and frame tie-down connectors.

Specifications subject to change without notice.